


LXA-1400

675+675 WATTS ■ AC Operation



New 1350 Watts Direct Coupled Amplifier with attractive most modern aesthetics, combined with legendary Ahuja ruggedness and reliability.

- Dual channel direct coupled amplifier.
- 1350 Watts rated output.
- Rugged, reliable and designed to work continuously under stringent conditions
- High fidelity sound.
- Ideal for high end music programmes.

SPECIFICATIONS

CONTINUOUS RATED POWER

STEREO/MONO 8 Ω : 2 × 250W, 4 Ω : 2 × 475W
2 Ω : 2 × 675W

BRIDGED OUTPUT 8 Ω : 950W, 4 Ω : 1350W

THD + N < 1.0%

FREQUENCY RESPONSE (-1DB) 20-20,000HZ

POWER BANDWIDTH (0.5% THD) 20-20,000HZ

INPUT SENSITIVITY 0dBm (775MV)/1.23V (SELECTABLE)

INPUT IMPEDANCE 10K UNBALANCED, 20K BALANCED

S / N RATIO > 95dB

CHANNEL SEPARATION > 65dB AT 1KHZ

DAMPING FACTOR 400 : 1 (8Ω)

SLEW RATE 35V/μS

PROTECTIONS TEMPERATURE, DC, RFI, SHORT CIRCUIT, OVERLOAD, BUILT-IN LIMITER, AC: FUSE 10AMP. (T 10A L);
± DC: FUSE 2 X 10AMP. (T 10A L) FOR EACH ZONE, ± DC: FUSE 2 X 2AMP. (FOR FAN SUPPLY)

INPUT CONNECTORS 2 × XLR, STEREO PHONE JACK 6.3MM

OUTPUT CONNECTORS SPEAKON 4-WAY, HEAVY DUTY BINDING POST FOR EACH CHANNEL

COOLING VARIABLE SPEED DC FAN WITH TEMPERATURE SENSING

FRONT PANEL CONTROLS 2 × 21 STEP LEVEL ATTENUATORS

INDICATORS POWER ON, SIGNAL, CLIP, TEMPERATURES, PROTECT (CH. A & B)

POWER CONSUMPTION (RATED) 1800VA @ 240V / 50Hz

DIMENSIONS W482 × H113 × D460 mm

WEIGHT 14.7kg